

HEAVY DUTY OPERATOR FOR CLASS I, II, III & IV INSTALLATIONS



*The **Leader Plus** combines engineering innovation and reliability with superb styling; unique two-stage drive system allows manual operation in the event of a power failure.*

LEADER PLUS

Slide Gate Operator - Model LP 1000

MAX Gate Length: 35 FT.

MAX Gate Weight: 1100 lbs.


Features

- CGA2K™ Technology
- UL325 & 991 Listed
- Rated for Continuous Duty
- Durable, Architecturally Designed Weather-Resistant Cover
- Cam-Driven Switches for Limits
- Built-In Maximum Run Timer for Added Safety
- Built-In Adjustable Auto-Close Timer
- Built-In Master/Slave Capability
- 13 Diagnostic LED's for Easy Service

- Easy Conversion Right-Hand/Left-Hand Drive
- Welded Uni-Body Frame with Power Coated Finish
- #41 Steel Roller Chain
- Pre-wired 9931FC Receiver

Options

- Radio Controls
- Standby Power Supply (battery backup)
- Chain Disconnect
- Photobeams
- Electric Edges
- 220V Operation
- #50 Roller Chain
- Traffic Control Devices



CGA2K™ Technology

Standard On Every Allstar Gate Operator

Features

- UL325 & 991 Listed
- Independently Adjustable Open & Close Inherent Anti-Entrapment System
- Selectable Control by Additional Operator (Master/Slave)
- Adjustable Auto-Close Timer (off, 2-60 seconds)
- Self-Adjusting Maximum Run timer

- Detected Entrapment Alarm
- Electronic (Dynamic) Braking
- Secure-Safe™ Pushbutton Control (patent pending)
- Separate Inputs for Access Control Devices and Entrapment Protection devices

WEST COAST

Toll Free: 877-356-2093

Local: 602-437-1680

FAX: 602-437-1804

e-mail: info@allstarcorp.com

EAST COAST

Toll Free: 877-441-9300

Local: 610-873-6900

FAX: 610-873-6953

web site: www.allstarcorp.com

Allstar

c.p. Allstar Corporation, Downingtown, PA 19335