

PULLING ACCESSORIES



Pulling Harnesses

- Designed to pull in 2" and larger conduit
- Harness legs are 1/4" galvanized aircraft cable
- Staggered grips on each double leg harness to avoid interference with each other
- Harnesses available in long and short lengths
- Grips have 5/8" diameter opening and are supplied with 2 jam screws
- See maximum capacities listing below



Pulling Harness Kits

Catalog Number	Description	Weight
2500	Includes 1 each of the following: 2502 – Clevis 2500-1 – Double Leg Pulling Harness – long 2500-2 – Double Leg Pulling Harness – short 2500-3 – Allen Wrench 3/8" 2500-4 – Allen Wrench 1/4"	5 lbs.
2501	Includes 1 each of the following: 2500-1 – Double Leg Pulling Harness – long 2500-2 – Double Leg Pulling Harness – short 2500-3 – Allen Wrench 3/8"	2 lbs.

Individual Harnesses

Catalog Number	Description	Weight
2500-1	Double Leg Pulling Harness – long	2 lbs.
2500-2	Double Leg Pulling Harness – short	2 lbs.

Clevis

Catalog Number	Description	Weight
2502	Clevis Max. Rated Capacity – 6,500 lbs.	1.2 lbs.

Maximum Capacities

The following are MAXIMUM pulling capacities:

- 1,750 lbs. maximum when using 1 grip of a double leg pulling harness
- 3,250 lbs. maximum per double leg pulling harness when using both grips of a double leg pulling harness
- 6,500 lbs. maximum when using both (Model 2500-1 and Model 2500-2) double leg pulling harnesses
- Clevis maximum capacity is 6,500 lbs.

www.currenttools.com

P.O. Box 17026 • Greenville, SC 29606 • 864.244.1201 • fax 864.244.5860 • 800.230.5421



Current Tools
FOR THE PROFESSIONAL ELECTRICIAN