

26 - Bit Wiegand Card Reader



FEATURES

- Interface with AeGIS 9000 Series (installed inside or outside the system). * Use AMPGB if mount outside the AeGIS 9000 Series.
- 4-wire connection.
- Weather-resistant housing for mounting outdoors.

SPECIFICATIONS

Power Input: 5.0 - 18 VDC Regulated (5 VDC is supplied by the AeGIS 9000 Series).
Current Consumption: 40 mA @ 5.0 - 12.0 VDC.
Dimension: 5.0" x 1.6" x 1.0"
Transmit Frequency: 125 Khz
Output Data: Data 0 and Data 1 standard Wiegand electrical and protocol interface.
Operating Environment: -22°F to +155°F Humidity 0-95% non-condensing.

Cable Distance: 500 feet maximum.
Mount: Outdoor or Indoor.
Shipping Weight: 2.0 Lbs approximate.
Enclosure: Slim weatherized housing, mounts on metal or other surface without regard to read performance.
"TWO YEARS WARRANTY" includes lightning and power surge if Pach and Company surge protector (ASP1) is installed).

ORDER PART NUMBER

AWCR: 26-Bit Wiegand Card Reader.
AISO: ISO 26 Bit Wiegand Card (credit card size).
ACLAM: Clam Shell 26 Bit Wiegand Card.
AFOB: 26-Bit Wiegand Key Fob.