550P MICRO LITE II™ STROBE

Single Flash Strobe

The model 550P family is a low profile single flash strobe light featuring a multiple input voltage rating of 12 thru 74 VDC, universal mounting, Lexan® lens, hi-efficiency regulated solid state potted power supply, and heavy duty xenon strobe lamp. All units are polarity protected and have built-in filters to protect against radio interference and spike voltages. The model 550P features a field replaceable plug-in strobe lamp and is UL component recognized for use on type E, EE, and ES electric industrial trucks covered by UL standard #583 under file number AU2049.

ORDERING INFORMATION

Please specify lens color and the model number desired. Colors available are AMBER, BLUE, CLEAR, GREEN, or RED.

Model No.	Description	Voltage
550P–1274	Single Flash Strobe	12 thru 74VDC
550PMB–1274	Magnetic Base with Coil Cord	
550PMBSC–1274	Magnetic Base with Straight Cord	
Options		
BKT	Mounting Bracket	
/LBO–MINILITE	Lens Blackout Segment 180°	
802–03	Lens Dust Cover (Not Shown)	
G802	Guard	
TBO–MAXI	Top Lens Blackout	
800–FLG	Flange Mounting Ring	
MINILITE SHIELD	Vinyl 180° Shield (Not Shown)	
550P–BASE	12–74VDC Power Supply	
550PMB–BASE	12–74VDC Power Supply with Mag & Coiled Cord	
550PMB–SCBASE	12–74VDC Power Supply with Mag & Straight Cord	

Ordering Example

Model No		Options
550P–1274–AMBER	+	TBO–MAXI

Note: *All "/" options are factory installed only.*

SPECIFICATIONS

Lamp Type
2001 Xenon Strobe Lamp

Lens Type
801–L–COLOR (Please Specify Color)

Voltage and Amperage
12–74VDC Draws 1.25 A avg. @ 12VDC tapering to .20 A avg. @ 74VDC

Power Supply Output 11 Watts
12 Joules per Flash

Flash Rate
70 to 90 Flashes per Minute

Intensity

CLEAR	270 Candela eff.
AMBER	230 Candela eff.
BLUE	125 Candela eff.
RED	55 Candela eff.
GREEN	110 Candela eff.

Size and Weight DWG 11515

5.25" Tall	x	5.5" Dia.	2.0 lbs.
(133 mm)		(140 mm)	(0.9 kg)

2100 WEST OBISPO
GILBERT, AZ. 85233

TOMAR®

PHONE: 800–338–3133
FAX: 800–688–6627