



The model 700 MINI STROBE family is a single flash heavy duty strobe light featuring an all aluminum housing, flange mounting, 360° Lexan® lens, hi-efficiency regulated solid state power supply and a plug-in field replaceable heavy duty xenon strobe lamp. The 700-1274 will operate over 12 thru 74 VDC without making any changes or adjustments. Most models are UL component recognized for use on type E, EE, and ES electric industrial trucks covered by UL standard #583 (UL File #AU2049).

ORDERING INFORMATION

Please specify lens color and the model number desired
Colors available are AMBER, BLUE, CLEAR, GREEN, or RED.

Model No.	Description	Voltage
700-110-15J	Single Flash, 15 Joule	120VAC
700-110	Single Flash	120VAC
700-240	Single Flash	240VAC
700-1274	Single Flash, UL recognized	12 thru 74VDC
700-120DC	Single Flash, UL recognized	120VDC

Mounting Options

/PM1	1/2" Pipe Mount
/M	Magnetic Mount #90 Magnet

Other Options

/GM	Guard
/CP	9' Straight Cord and Cigar Plug (Not Shown)
/LBO-MINI	Lens Blackout Segment 180°
/CC	10' Coil Cord with Cigar Plug
BKT	Bracket with U Bolts
/DEMO	Demo Prep with Battery Clamps
MICROSHIELD	Vinyl, 180° Lens Blackout (Not Shown)
700-DC	Clear Lens Dust Cover (Not Shown)

Ordering Example

Model No.	Option
700-1274-AMBER	+ /M/CC

Note: All "/" options are factory installed only

SPECIFICATIONS

Lamp Type	Lens Type	
3001 (700 Family)	700-L (specify color)	
6001 (700-110-15J)		
Voltage and Amperage		
12-74VDC	Draws	1.25 A avg. @ 12VDC tapering to
		0.2 A avg. @ 74VDC
120VAC	Draws	0.17 A avg.
120VDC	Draws	0.1 A avg.
240VAC	Draws	0.12 A avg.
Power Supply Output 11 Watts		
8 Joules per Flash	Standard Units	
15 Joules per Flash	Model 700-110-15J	
Flash Rate		
80 to 95 Flashes per Minute		
Intensity		
Lens Color	8 Joule	15 Joule
CLEAR	185 Candela eff.	360 Candela eff.
AMBER	160 Candela eff.	300 Candela eff.
BLUE	85 Candela eff.	160 Candela eff.
RED	40 Candela eff.	80 Candela eff.
GREEN	70 Candela eff.	140 Candela eff.
Size and Weight		
6" Tall (152 mm)	x 4.7" Dia. (119 mm)	1.3 lbs. (.58 kg)